

Three Faces of Wire Cell Prototype, Toolkit, Integration

Brett Viren

Physics Department



WC LEE And
2017 May 22

Outline

Overview

Prototype

Toolkit

- Command Line Interface

- Packages

- Class Interfaces and Components

- Configuration

- Utility Code

- Coding Conventions

- Unit Tests

- Python

- Documentation

Integration

What's in a name

Wire – Cell

some post-hoc philosophizing

- wire** embodies a measurement
- cell** represents an ideal truth
- indicates their connection

Three Code Bases of Wire – Cell

Wire – Cell software spans three distinct collections of packages:

① Wire – Cell Prototype (WCP):

→ initial algorithm development, tryout new ideas, don't worry (too much) about code perfection.

② Wire – Cell Toolkit (WCT):

→ production quality coding, high performance and long term maintenance.

③ Wire – Cell Integration (WCI):

→ use of WCT components by LArSoft.

- Typically, development of algorithms proceed in order: WCP→WCT→WCI.
- WCP devel may be skipped if WCT-quality design is already understood.
- WCI devel is only needed when new, major **Interfaces** are developed.

Wire – Cell Source Code Organizations

prototype <https://github.com/BNLIF/>

toolkit <https://github.com/WireCell/>

integration <https://cdcvcs.fnal.gov/redmine/projects/larwirecell>

- Prototype and Toolkit each consist of a set of multiple `git` repositories.
- Integration consists just the one under the greater `larsoft` UPS umbrella product.

Documentation

prototype <http://bnlif.github.io/wire-cell-docs/>

- Source in Markdown/`mkdocs`, read as HTML.
- Not always maintained, but still useful.

toolkit <https://wirecell.github.io/>

- Source in Org, read as HTML/EPUB/PDF/Markdown/Org.
- Intended to be up to date but not full coverage yet.
- Documentation framework may change.

integration <https://cdcvns.fnal.gov/redmine/projects/larwirecell/wiki>

- Just the wiki, essentially empty.
- We should flesh it out after the next WCI push.

Developer Installation: WCP

Source is aggregated with `git submodules` and built with **Waf**.

```
git clone --recursive git@github.com:BNLIF/wire-cell.git wcp  
  
cd wcp/ && alias waf=$(pwd)/waf-tools/waf  
  
waf --prefix=/path/to/install configure build install
```

Thereafter, to rebuild/reinstall:

```
waf install
```

See documentation for user install.

Developer Installation: WCT

Source is aggregated with `git submodules` and built with **Waf**.

```
git clone --recursive git@github.com:WireCell/wire-cell-build.git wct
cd wct/ && alias waf=$(pwd)/wcb
waf --prefix=/path/to/install configure build install
```

Thereafter, to rebuild/reinstall:

```
waf install
```

See documentation for user install.

Pulling, Committing and Pushing Commits

WCP/WCT currently use **git submodules**. So, two step pull:

```
git submodule foreach git pull
git pull
```

To commit and push is also a two step:

```
cd <pkg>/ && hack
git commit -am "My great hack."
git push

cd ..
git commit -am "Pick up update to <pkg>."
git push
```

NB: The **larwirecell** integration code in a single Git repo so apply the usual Git commands. FNAL recommends following **git flow**

Installation of Software Dependencies - WCP/WCT

WCP and WCT can share same set of “external” packages.
Provide them however it is convenient:

- Install OS packages.
 - Ubuntu has most required packages except ROOT6
- Manually install each from source.
- Automate installation with Spack.
 - This is the recommended approach.
- Use existing binaries
 - Eg, using UPS products at Fermilab
- Some mixture of the above.

Learn how to teach `waf` locations of externals:

```
waf --help
```

Installation: WCI

- WCT is UPS product `wirecell`, WCI is `larwirecell`
- New releases (and their externals) are built to UPS products by FNAL
 - Requests should ultimately go through Redmine tickets.
 - Asking Lynn Garren or LARSoft mgt directly is a good start.
- WCI developer follows “standard” Fermilab way (`ups`, `mrbs`, etc).
- **TODO:** we must learn to build `wirecell` UPS product ourselves:
 - Often we have to make fixes to accommodate FNAL problems.
 - Best if we can test full stack at FNAL before making a WCT release.
 - Best if we can make simultaneous WCT+WCI releases.
 - Having FNAL in this test/release loop adds too much delay and confusion.

Ideas to make WCI development easier for us have been proposed but FNAL has responded negatively.

Overview

Prototype

Toolkit

Integration

A few random comments about WCP devel

- Coordinate any development with Xin.
 - I'll also try to help, but I give WCP very little attention.
- Do not modify existing code without original author's permission.
 - Use `git blame` or GitHub's [Blame] button to find author.
- Okay to copy-and-modify but **must not** reuse same class names.
 - Feel free to make new WCP packages in BNLIF GitHub org.
- Develop prototype as "throw-away" or "first draft" code.
 - Don't get too "attached".
 - WCP and WCT classes and patterns differ but many concepts the same.
 - Long term, code needs to be "ported" to WCT where much **stricter code quality control** will be enforced and only **limited external dependencies** will be allowed in "core" libraries. Preparing for that in WCP makes porting easier.

With that, WCP is a playground, enjoy playing and be creative!

Overview

Prototype

Toolkit

- Command Line Interface

- Packages

- Class Interfaces and Components

- Configuration

- Utility Code

- Coding Conventions

- Unit Tests

- Python

- Documentation

Integration

Wire – Cell Toolkit Caveats and Concerns

- There is a lot of “stuff” in Wire – Cell Toolkit.
- Not everything is yet perfectly documented.
- Not everything is even yet perfectly conceptualized or designed.
- **It is ready for contributions from others.**
- However, **please tread lightly**, ask questions, understand intentions.
- Before diving in there should be an informal discussion of scope, design, dependencies, etc.
- Some things can still change, but a lot of things must stand firm.
- I want us to resist making compromises just to satisfy near-term time pressures.

Wire – Cell Toolkit Caveats and Concerns

- There is a lot of “stuff” in Wire – Cell Toolkit.
- Not everything is yet perfectly documented.
- Not everything is even yet perfectly conceptualized or designed.
- **It is ready for contributions from others.**
- However, **please tread lightly**, ask questions, understand intentions.
- Before diving in there should be an informal discussion of scope, design, dependencies, etc.
- Some things can still change, but a lot of things must stand firm.
- I want us to resist making compromises just to satisfy near-term time pressures.

Okay, on to the technical stuff→

Overview

Prototype

Toolkit

- Command Line Interface

- Packages

- Class Interfaces and Components

- Configuration

- Utility Code

- Coding Conventions

- Unit Tests

- Python

- Documentation

Integration

Command Line Interface

WCT is a **toolkit** but also provides the **wire-cell** command line application exposes WCT functionality to the user.

Eg, to run the simulation:

```
wire-cell -c uboone/fourdee.jsonnet
```

Has brief online help

```
wire-cell --help
```

Cmdline arguments that:

- Set one or more “app” **components** to run.
- Load **plugin** libraries that provide components.
- Give one or more **configuration** files.
- Dump hard-coded default configuration.
- Override individual configuration parameters (still todo!)

Overview

Prototype

Toolkit

Command Line Interface

Packages

Class Interfaces and Components

Configuration

Utility Code

Coding Conventions

Unit Tests

Python

Documentation

Integration

Package Names and Layout

WCT (and WCP) packages follow fixed layout conventions:

name source package is `wire-cell-<name>`, submodule directory is `<name>/`, shared library, include dir and package name for build system dependencies is `WireCellName`

src/ holds `.cxx` implementation and private `.h` headers for a shared library and `wscript_build` connection to build system.

inc/WireCellName/ holds public `.h` headers.

test/ holds unit test `test_*.cxx` source.

apps/ in rare packages, holds code for `main()` programs.

Note: any “public” Python modules/programs should likely be put in `wire-cell-python` package rather than spread among individual packages.

Package Build System

The build system is almost invisible.

Each package needs one file, `wscript_build`, holding a single function declaring the **package name** and connections into **three dependencies trees**:

```
bld.smplpkg("WireCellGen",           # required
            use="WireCellIface WireCellUtil", # optional, likely
            test_use="WireCellRootVis",      # optional, likely
            app_use="DYNAMO BOOST")          # optional, unlikely
```

`use` packages on which the shared library depends

`test_use` (optional) if package's unit tests require more dependencies.

`app_use` (optional) if package has applications and they require additional dependencies.

NB:

- “Core” WCT libraries have very restricted dependencies (eg, no ROOT).
- Most packages **should not** have applications as this is what `wire-cell` is for.

WCT Package Dependency

wire-cell-*
(implementation packages)
wire-cell-iface
(interface classes)
wire-cell-util
(infrastructure and utilities)
external dependencies
(Boost, Eigen3, FFTW3)

- Implementation packages **must not** depend on one-another.
- Optional packages may have optional dependencies. Eg, `wire-cell-tbb` implements Wire Cell data flow programming (DFP) using/requiring Intel TBB.
- Some optional dependencies are handled by compile-time switches in the code, Eg. optional Jsonnet support.

Overview

Prototype

Toolkit

Command Line Interface

Packages

Class Interfaces and Components

Configuration

Utility Code

Coding Conventions

Unit Tests

Python

Documentation

Integration

WCT Interfaces

Major toolkit functionality is exposed via “**Interfaces**”

- An Interface is an *abstract base class* defining the *virtual methods* to be implemented by a subclass.
- Interface **method arguments** must be:
 - Other Interfaces (typically via `shared_ptr<>`)
 - Classes or types defined in `wire-cell-util`
 - Plain old data types (`int`, etc)
 - STL containers of PoD (`std::vector<float>`, etc)
 - **Must not** reference types specific to another toolkit/framework.
 - `no TH1F, no recob::Wire`
- All Interface classes live in `wire-cell-iface`.
- Interfaces have some inheritance hierarchies:
 - `INode` data flow programming nodes
 - `IData` data products passed between nodes

Data Interfaces

`IData` is base to all data interfaces, provides pointer and vector typed on the subclass (`C RTP`).

Some examples:

- `IDepo` point energy deposition (x, y, z, t, q) with optional transverse and longitudinal extent.
- `IWire` a wire segment in a wire plane leading to a channel.
- `ICell` an association of crossing wires.
- `ITrace` a waveform fragment in a channel at a given time.
- `IFrame` a collection of traces (aka “event”/“trigger”)

There are various more and we can make new ones as needed, but with a lot of thought.

Why Data Interfaces?

It is somewhat unorthodox to have interfaces for data objects.

- As a toolkit, WCT must deal with “foreign” data classes from other applications/frameworks.
 - Want to avoid unnecessary copies.
 - Interfaces allow building of facades.
- Do not want to dictate user representations.
 - One user may have some backing database for some objects.
 - Another may have load-on-demand files.
 - A third may want to copy objects bodily.
- Data Flow Programming places some restrictions.
 - Nodes always pass `shared_ptr` to interface or collections of these shared pointers.

NB: `wire-cell-iface` provides a set of `Simple*` concrete data classes which are trivial bags of data. Implementation code is free to use these if suitable.

DFP Node Interfaces

A Data Flow Programming (DFP) node Interfaces specify:

- data types for node input or output.
- whether node instances are safe to run concurrently.
- the node “category” (DFP connecting behavior, “source”, “sink”, “function”, “queued”, etc)

Some DFP node category Interfaces:

- `IFunctionNode` stateless, function-like node.
- `IQueuedNode` object in, collection out, caching.
- `ISourceNode` provide an object each call.
- `ISinkNode` consume an object each call.
- **others:** `IFaninNode`, `IJoinNode`, `IHydraNode`

NB: Nodes are used even if app does not use full DFP feature.

Typed Node Interfaces

Subclasses of a node category Interface fixes the data types.

- `IDepoSource` source of energy depositions (“depos”)
- `IDrifter` queued, drifting of depos.
- `IDuctor` consume depos, produce frames applying induction (field + electronics response).
- `IFrameSource` generate frames (eg, a for a noise source)
- `IFrameFilter` frames in, frames out (eg, digitizer)
- `IFrameSink` consume frames (eg, to writing output file)

Other Interfaces

Some Interfaces simply provide some general functionality.

- `IWirePlane` info about one plane of wires, includes logical wire geometry, field response, vector of `IWire` objects.
- `IAnodeFace` info about wire planes on one face of an anode plane.
- `IAnodePlane` (“APA”) info about one or two anode faces, includes wire/channel map.
- `IRecombinationModel` simple function to convert energy deposition to number of drifting electrons.
- `IApplication` a main WCT “app” component with an `execute()` method. (akin to Gaudi Algorithm or *art* Module).

WCT Components

A WCT **component** is an **object instance** of an **implementation** (subclass) of one or more WCT **interfaces**.

- Think: *an actor in a play satisfying one or more roles*.
- Some may be small and simple (eg a recombination model) or large and complex (eg, the simulation “app”).
- Components may use other components.
- Components are **dynamically constructed**
- They are stored and located via two string labels:
 - type** typically (but not necessarily) the implementation class name with any `namespaces` removed. Must be unique.
 - name** labels a unique instance of a **type**. If only one instance needed, name is often left blank.

Note: the **type/name** pair is also used in configuration.

Drifter - extended example

The “Drifter” component from `wire-cell-gen`

- Component **type**: `Drifter`
- C++ class name: `WireCell::Gen::Drifter`
- Definition file: `Drifter.h`
- Implementation file: `Drifter.cxx`
- Interfaces: `IDrifter` and `IConfigurable`

Features:

- Is user configurable
- Transports energy depositions in space and time
- Uses a uniform drift velocity vector field.
- Drift stops at a “*field response plane*” near the wires.
- Applies physics: recombination, absorption, diffusion, statistics.

So far it is the only `IDrifter` but there could be others, eg:

- `SCEDrifter` might handle space-charge effects.
- `GArDrifter` might handle gaseous argon drifting.

Drifter - example component definition

Drifter is both an IDrifter and an IConfigurable.

```
#ifndef WIRECELL_DRIFTER    // include
#define WIRECELL_DRIFTER    // guards
#include [...] // snipped for brevity

namespace WireCell { namespace Gen {

class Drifter : public IDrifter, public IConfigurable {
public:
    // IDrifter interface
    virtual bool operator()(const input_pointer& depo,
                           output_queue& outq);

    // IConfigurable interface [snipped for later]

    // ... local methods and data members ...
}; }}
#endif
```

Showing just IDrifter interface method here.

Drifter - example component implementation

```
#include "WireCellGen/Drifter.h"
#include "WireCellUtil/NamedFactory.h"

WIRECELL_FACTORY(Drifter,                                     // (1)
                  WireCell::Gen::Drifter,                   // (2)
                  WireCell::IDrifter, WireCell::IConfigurable); // (3)

//... actual implementation code...
```

A CPP macro is used to “register” the component via args:

- 1 the **type** label described above.
- 2 the fully namespace-qualified C++ class name.
- 3 list of all interfaces this component class implements.

Drifter - example component lookup

```
#include "WireCellUtil/NamedFactory.h"
#include "WireCellIface/IDrifter.h"
using namespace WireCell;

// ... later in some method ...

string type = ..., name = ...;

auto drifter = Factory::lookup<IDrifter>(type, name);
```

- Look up component by **type** and **name**, typically as provided to user code via configuration. Code should **not** “care” their values.
- Component returned as a `shared_ptr<InterfaceType>`, memory management is automatic.
- The component should be considered pre-configured, ready to use.
 - It is up to the application layer (`wire-cell` or `WCI`) to assure this.
- Some overhead so do not do `lookup` inside a tight loop!

Overview

Prototype

Toolkit

- Command Line Interface

- Packages

- Class Interfaces and Components

- Configuration**

- Utility Code

- Coding Conventions

- Unit Tests

- Python

- Documentation

Integration

WCT Configuration Rules

Most WCT components:

- **should be** parameterized to the **greatest extent possible**.
- **must not** use hard-coded numbers!
- **should** provide sane, hard-coded **parameter defaults**.
- **must not** use hard-coded numbers!
- **must not** use hard-coded numbers!

Drifter - example configurable

```
#include "WireCellIface/IConfigurable.h"
#include "WireCellIface/IDrifter.h"

namespace WireCell { namespace Gen {

class Drifter : public IDrifter, public IConfigurable {
public:

    // Provide hard-coded "sane" defaults.
    virtual WireCell::Configuration default_configuration() const;

    // Accept config object from user.
    virtual void configure(const WireCell::Configuration& config);
    // ...
}; }}
```

- Inherit from `IConfigurable` in addition to other interfaces.
- Declares `IConfigurable`'s two methods (others not shown).

Code Strategies for Configuration

Driven by:

- You **should** write unit tests for your components.
- Unit tests **may** directly instantiate concrete components.
- Concrete components **may** provide direct configuration methods.
- You **should** avoid separate paths for configuration information.

Recommend following this “configuration flow” pattern:

- 1 Place “sane” hard-coded defaults as constructor arguments and store as data members.
- 2 Return default configuration object based on these.
- 3 Use them as defaults when unpacking a configuration object passed in.

NB: some WCT code may fail to follow this pattern, consider that a bug needing fixing.

Configuration Code Strategy Example

```
namespace WireCell { namespace Gen {  
  
class MyComponent : public IConfigurable {  
    int m_a; double m_b;  
public:  
    // hard-code and store "sane" defaults here  
    MyComponent(int a=42, double b=6.9) : m_a(a), m_b(b) {};  
    // pass defaults to user  
    Configuration default_configuration() const {  
        Configuration cfg;  
        cfg["a"] = m_a;  
        cfg["b"] = m_b;  
        return cfg;  
    }  
    // use as defaults when unpacking user's config object  
    void configure(const Configuration& cfg) {  
        m_a = get(cfg, "a", m_a);  
        m_b = get(cfg, "b", m_b);  
    }  
    // ...  
};};}
```

Note: implementation is in header just for brevity here.

Configuring Components

Manual configuration of component objects is allowed and useful in:

- Writing unit tests.
 - eg setting parameters directly for brevity.
- Developing integration code.
 - eg converting from LArSoft's configuration object.

WCT automates component configuring with `ConfigManager`:

- Configuration actions driven by the configuration itself.
 - Iterates through configuration in strict order.
- Dynamically constructs components as they are discovered in the configuration.
- Matches portion of configuration to each component and applies it.
 - User config is merged into hard-coded default

Configuration Object Schema

In memory, configuration is a *heterogeneous, recursive* data structure `WireCell::Configuration`.

- It's really just a `Json::Value` (from JSONCPP)
- Top level configuration object is an array (list).
- Each entry is an object (dictionary) with keys **type**, **name** and **data**.
- The **type** and **name** are used to match configuration to configurable component instance.
- The **data** attribute has a value which follows a **type**-specific schema.
- The **data** value is passed to `configure()`.

Example Configuration

Expressed as JSON, with two components both of type `MyComponent` (prior example) and with names `mc1` and `mc2`:

```
[
  {
    "type": "MyComponent",
    "name": "mc1",
    "data": { "a": 100, "b": 1.0 }
  },
  {
    "type": "MyComponent",
    "name": "mc2",
    "data": { "a": 200, "b": 2.0 }
  }
]
```

The `name` may be omitted and a default `" "` will be assumed.

Two Configuration File Formats

WCT accepts two types of configuration files:

JSON as described above, a simple list of configuration objects, one for every configurable component that might be used in an application.

Jsonnet a Turing-complete, JSON-like *data templating language* that **compiles into JSON**.

Why two?

- Code wants exhaustive, regular and lightly structured data.
- Humans want concise and highly structured, non-repetitive description of data.

WCT Jsonnet Overview

- Jsonnet is currently **optional** in WCT.
 - If compiled with support Jsonnet files can be directly read.
 - If user's install has no support, can install Jsonnet and use `jsonnet` command line program to compile to JSON.
 - You **really** want to use Jsonnet instead of plain JSON.
- Excellent docs on the [Jsonnet web site](#).
- See also configuration section of the [WCT Manual](#).
- The `wire-cell-cfg` package holds Jsonnet configuration and support.
- Jsonnet is similar in syntax and schema to FCL but it is somewhat more regular and has a super-set of features.

WCT Jsonnet Support

WCT provides `wirecell.jsonnet`

- Exports the WCT system-of-units to Jsonnet.
- Provides Jsonnet forms for common, low-level WCT objects
 - `Point`, `Ray`, `Component`
- Helpers for defining DFP graphs.
- Expect it will grow as needed.

Jsonnet Primer

Explore the current config for μ Boone sim.

Currently organized in three layers:

- global parameters
- define some default component configurations
- define actual configuration

(click to browse source)

This is just an initial organization. Want to factor out common configuration chunks shared between DUNE and μ Boone.

Configuration File Miscellany

- JSON and Jsonnet files are used for other input files:
 - Field response data files.
 - Wire geometry / channel map files.
 - Deposition files
- JSON and Jsonnet files are located first in the current working directory and then by searching a path list given by the `WIRECELL_PATH` environment variable.
- JSON (and not Jsonnet) files may be compressed with `bzip2` (use a `.json.bz2` extension).

Overview

Prototype

Toolkit

Command Line Interface

Packages

Class Interfaces and Components

Configuration

Utility Code

Coding Conventions

Unit Tests

Python

Documentation

Integration

Tour of `wire-cell-util`

Bottom of dependencies, it depends on no other WCT package.
Provides **low-level** and **general** classes and functions. Eg:

- `Binning` nbins, maxbin, minbin and related operations.
- `BoundingBox` operations to calculate 3D bounding boxes
- `Point`, `Ray`, `Intersection` 3D vectors
- `ExecMon` = `MemUsage` + `TimeKeeper`
- `String` string functions, eg `split()`.
- `Type` turn C++ types into human readable strings.
- `Pimpos` pitch-impact-position operations
- `Response` field+elec response support.
- `Waveform` for real and complex arrays and FFT.
- `Patterns`: `Interface`, `Iterator`, `NamedFactory`, `Singleton`,
- `Managers`: `PluginManager`, `ConfigManager`

NB: some things probably should become components!

Units

It is **mandatory** that WCT system-of-units is obeyed.

This means any **quantity with units**:

- held in a variable in WCT C++, Python or Jsonnet code **must** be considered expressed in the WCT system-of-units.
- expressed as a literal number in WCT C++, Python or Jsonnet code **must** have a unit **multiplied**.
- **may** be expressed in alternative units if consumed **immediately** (eg, for formatted output) by dividing by a WCT unit symbol.
- expressed as a literal number in JSON or other representation where explicit units are not supported **must** be implicitly in WCT system-of-units.

Units - Literal Values

```
// C++  
#include "WireCellUtil/Units.h"  
double drift_speed = 1.6*units::mm/units::us;
```

```
# Python  
from wirecell import units  
drift_speed = 1.6*units.mm/units.us
```

```
// Jjsonnet  
local wc = import "wirecell.jsonnet";  
{ drift_speed: 1.6*wc.mm/wc.us, ... }
```

- Never write a quantity as a bare number without a WCT unit.
- Never have a variable hold a quantity outside WCT system-of-units.

Units - Conversion On Output

May convert units when value is immediately consumed

```
// C++  
cout << "Drift speed is " << v/(units::mm/units::us) << " mm/us\n";
```

```
# Python  
print ("Drift speed is %f mm/us" % v/(units.mm/units.us))
```

Other contexts to convert to some explicit units:

- Booking histograms to use appropriate ranges.
- Writing output in formats assuming other system of units.
- Note, integration code may hold values in other than WCT system-of-units but must convert when calling WCT code.

Overview

Prototype

Toolkit

Command Line Interface

Packages

Class Interfaces and Components

Configuration

Utility Code

Coding Conventions

Unit Tests

Python

Documentation

Integration

Coding Conventions

Covers:

- Formatting (use one the true indent = 4 spaces).
- Commenting conventions.
- Usage of C++ `namespace`.
- Class, method and variable casing and naming patterns.

Exhaustive list in [the WCT manual](#).

Would like to have some editor config to help us comply.

Overview

Prototype

Toolkit

- Command Line Interface

- Packages

- Class Interfaces and Components

- Configuration

- Utility Code

- Coding Conventions

- Unit Tests**

- Python

- Documentation

Integration

Unit Testing Philosophy

- As you develop some class or functions (units), you write tests.
- Write tests to **fail**, actually test things. Use `assert()` liberally.
- Write tests to be reproducible forever which means no input data nor parameters. For once, it's okay to hard-code!
 - if input data is truly needed, make it as small as possible so it can be included in the repo, even compiled into the code.
- Tests do not have to be beautiful or high-performance
 - but they get run a lot so don't make them overblown.
- Tests should be numerous and each should test a small part of some unit.
- Tests should not include large copy-paste from other tests.
 - Doing this means you are writing "real" code which should be cleaned up and moved into some library (and **it** should be tested)
- Tests are not applications, they should only test, not overloaded into also being "useful".

Writing WCT Unit Tests

- 1 Start a file under `<pkg>/test/test_name.cxx`.
 - Pick a name that describes the unit (eg, class name)
- 2 Inside make several `test_<testname>()` functions which take **no arguments** and each which tests some aspect of the unit.
- 3 Make a `int main()` function that takes **no arguments** and which calls all the test functions.

```
#include "WireCellUtil/Testing.h"
using namespace WireCell;
void test_something() {
    // ...
    int val = some_function();
    Assert(val == 42);
}
int main() {
    test_something();
    return 0;
}
```

Running WCT Unit Tests

- Unit test are built automatically by `waf`.
- `waf` will **try** to run them, but they will fail by default due to environment issues.
- To make it work `waf` needs know how to set a run-time environment. You can set this up in your own shell but that can interfere with build dependencies.

If `$install` points to the installation directory:

```
# first build without running tests
waf --notests build install
# then run all tests using proper harness
waf --alltests --test-cmd="LD_LIBRARY_PATH=$install/lib %s"

# or, run an individual test by hand:
LD_LIBRARY_PATH=$install/lib ./build/<pkg>/test_<name>
```

This needs some improvement!

Overview

Prototype

Toolkit

- Command Line Interface

- Packages

- Class Interfaces and Components

- Configuration

- Utility Code

- Coding Conventions

- Unit Tests

- Python

- Documentation

Integration

WCT Python Support

wire-cell-python

- Currently a pure-Python package.
- Uses standard Python `setup.py` packaging.
- Wire – Cell system-of-units
- Provides `wirecell` Python module tree and `wirecell-*` main programs using Click CLI.
- Conversion from external config formats (eg, Garfield), generators of config (eg, wires) and tests and plots.
- Various proofs of principle and prototypes.

May extend to allow using WCT components in Python.

Overview

Prototype

Toolkit

- Command Line Interface

- Packages

- Class Interfaces and Components

- Configuration

- Utility Code

- Coding Conventions

- Unit Tests

- Python

- Documentation

Integration

Types of Documentation

- Formal manual.
- Doxygen reference.
- GitHub READMEs, issues, pull-requests

Authoring and Building Manual Text

Source at `docs/manual/` and generated content at <https://wirecell.github.io/>.

- Currently written in **Org** markup language.
- Uses `waf` to build the output formats.
 - Needs Emacs and some Emacs packages installed.
- A few caveats:
 - Emacs is best for writing Org, but not required.
 - The build is currently not tested outside my environment.
 - Some things about the current manual system I don't like and will probably change.

Reference Documentation

- Follow Doxygen commenting rules for any comments that you want to show up in the reference documentation.
- All Interface headers **must** have per-class and per-method Doxygen comments.
 - Some may lack it - this is considered a bug.
- Implementations headers **may** have Doxygen comments.
- Doxygen comments **should not** be used for implementation comments.
- Implementation comments **may** be used.
 - Opinion: Comments always lie. It is far better to spend energy to use **descriptive names** for variables, functions and classes.

NB: Generating Doxygen reference documents is not yet automated and served. Volunteer?

Overview


Prototype

Toolkit

Integration

Integration Strategy

- WCT Interfaces and components are similar in concept to *art* Tools
- Any WCT component we expose to LArSoft write an *art* Tool which:
 - Inherits from desired WCT Interface
 - Inherits from LArSoft Tool base class (interface)
- Design *art* Tool side to either accept LArSoft data objects or PoD.
- Some more design details still need to be developed.



The WCT `Fourdee` simulation app component which orchestrates various subcomponents. The input and output components are implemented as (also) *art* Tools.

Integration Tasks

- Use currently integrated WCT Noise Filtering as vehicle for:
 - Test out the Integration Strategy above.
 - As side effect clean up WCT and WCI parts.
 - Test out ways to handle configuration exchange.
 - This task is for me.
- Integrate existing WCT simulation.
 - This task is for Brian after I provide more concrete guidance based on the above.
- Integrate WCT signal processing once ported from WCP.
 - ditto